



**HFC500 | HFC750 | HFC990**

# FUEL CART



Model	Tank Capacity	Empty Weight	GVWR
HFC500	500 gallon	2700 lbs.	7000 lbs.
HFC750	750 gallon	2900 lbs.	12000 lbs.
HFC990	990 gallon	3100 lbs.	12000 lbs.



## Standard Features

- 10 Gauge double seam welded tank
- Tank is independent of the chassis and can be removed
- Protective material applied to the underside of tank serving as a fender
- Full length baffled tanks (two baffles per tank)
- 3/4" anti-slosh tank vent and fill cap vents at 2.5 PSI
- 1-1/2" drain plug
- Tank is flanged at bottom towards front for complete draining
- Electric brakes with breakaway system and safety chains
- 25 GPM 12 volt fuel pump, battery and 1"x 35' hose with retractable reel and auto shut-off nozzle
- 10 Micron filter
- Fuel gauge located on top of tank with infinite fuel level indicator
- Liquid - two component paint and primer
- 7000 lbs. square lift jack with bolt on plate for removal if jack gets damaged
- Dual torsion axles: 3500 lbs. on (HFC500) and 6000 lbs. on (HFC750/990)
- DOT approved incandescent tail lights, stop lights, front and rear side marker lights
- Adjustable 2-5/16" ball hitch
- Nose storage

Specifications are subject to change without notice.

## Options

- 40 GPM gas pump w/electric start
- Rock guard
- Custom paint (1 color)
- Aluminum rims
- 3" Pintle hitch
- Spare tire w/rim
- Auxiliary 60 gallon oil tank
- Insulated stainless steel 60 gallon DEF tank
- Insulated stainless steel 100 gallon DEF tank

ph: 1-800-446-8222 • fax: 507-847-5100 | 131 County Rd 34 E • Jackson, MN 56143

11202012

**www.hitchdoc.com | 1-800-446-8222**